Revised: April 11, 1983

U.S. DEPARTMENT OF LABOR

Form Approved
OMB No. 44-R1387

Occupational Safety and Health Administration.

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing.
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

1	SECTION	= -	HAZAR	SECTION II - HAZARDOUS INGREDIENTS _		
	PAINTS, PRESERVATIVES, & SOLVENTS	*	(חייף) ברא	ALLOYS AND METALLIC COATINGS	A	ייביא דיא
	MGMENTS (Carbon black)	13		BASE METAL		
	CATALYST		٠	уптом		
	VEHICLE (Resin	85		METALLIC COATINGS		
	SOLVENTS			PLUS COATING OF COME FLUX		
	ADDITIVES (Dye	2		OTHERS		
	OTHERS					
	HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	Q	инен полі	or solids or gases	8	דע. (לוחוש)
	Not applicable	Lica	able			
	•					
				•		
		·	÷			

	SECT	TON 111 - PI	SECTION III - PHYSICAL DATA	
BOUNG PONT ("F.)		N. A.	SPECIFIC GRAVITY (H2O-1)	1.2
VAPOR PRESSURE (mm Hg.)		N. A.	PERCENT, VOLATILE BY VOLUME (%)	N. A.
VAPOR DENSITY (AIR+I)		N. A.	EVAPORATION BATE 10	N. A.
SOLUBILITY IN WATER	-	Insolutie	Le	
APPEARANCE AND ODOR	Odorless black bowder	्र श्वेचात्	owder	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA	(PLOSION HAZARD DATA	
FLASH POINT (Method used)	FLAMMABLE LIMITS Let U.	-
EXTINGUISHING MEDA Water dry chemical		
SPECIAL FIRE FIGHTING PROCEDURES		
None		
UNUSUAL FIRE AND EXPLOSION HAZARDS		
None		*

::

EFFECTS OF OVEREXPOSURE Health EMERGENCY AND FIRST AID PROCEDURES Contact with skin: Normal Washing with soap and water. THRESHOLD LIMIT VALUE eyes: Try to remove or unsuccessful, toxic. hazard SECTION V -There is no health hazard in normal use condition. get medical attention. flush out with eye drops. is minimal, HEALTH HAZARD DATA being neither irritating, corrosive

STABILITY INCOMPATABILITY POLYMERIZATION HAZARDOUS DECOMPOSITION PRODUCTS (Materials to avoid) UNSTABLE WILL NOT OCCUR MAY OCCUR SECTION VI - REACTIVITY DATA None None 12. CONDITIONS TO AVOID normal in normal handling and use conditions to Avoid × handling and use

WASTE DISPOSAL METHOD If spilled, sweep up Disposal TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED should conform SECTION VII - SPILL OR LEAK PROCEDURES မ္ပ pick up g local by vaccuum cleaner regulation.

VENTILATION RESPIRATORY PROTECTION (Specify type) OTHER PROTECTIVE EQUIPMENT PROTECTIVE GLOVES MECHANICAL (General) None needed SECTION VIII . None needed Adequate SPECIAL PROTECTION INFORMATION None None needed needed ventilation EYE PROTECTION OTHER SPECIAL None needed

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING

Store in a cool and dry place.

Keep containers closed. Store other precautions
Do not handle in areas where Avoid inhalation of dust. the wind blows: flying powder may enter into eyes

PAGE (2)

RICOH PPC toner type 4000

Form OSHA-20 Nev. May 72

S. Shimizu General Manager P.L.P. Department