

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

age 1/7

1118869 5L Imagelink Microfilm Developer and Replenisher

Revision

evision data

Property and the second		Tovision date
SECTION 1: Identification	of the substance/mixture and of the company/undertaking	
1.1. Product identifier		
Product name	1118869 5L Imagelink Microfilm Developer and Replenisher	
1.3. Details of the supplier of	the safety data sheet	
Company	Eastman Park Micrographics 6300 Cedar Springs Road	
Address	Dallas, TX 75235	
Web	www.epminc.com	
Telephone	+1 866 934 4376	
Fax	+1-585-486-1902	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	C; R35 Xn; R40-68 Xi; R43 Symbols: C: Corrosive, Xi: Irritant,	
Main hazards	Causes severe burns. Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. Possible risk of irreversible effects.	
2.1.2. Classification - EC 1272/2008	Skin Corr. 1A: H314; Skin Sens. 1: H317; Muta. 2: H341; Carc. 2: H351;	

2.2. Label elements		
Hazard pictograms		
Signal Word	Danger	
Hazard Statement	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Skin Sens. 1: H317 - May cause an allergic skin reaction. Muta. 2: H341 - Suspected of causing genetic defects. Carc. 2: H351 - Suspected of causing cancer.	
Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.	
Precautionary Statement: Response	P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+P352 - IF ON SKIN: Wash with plenty of water/. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	

1118869 5L Imagelink Microfilm Developer and Replenisher

Revision

Revision date

2.2. Label elements

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P310 -Immediately call a POISON CENTER/doctor/ . P321 - Specific treatment (see on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P363 - Wash contaminated clothing before reuse. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Storage

Disposal

67/548/EEC / 1999/45/EC

Precautionary Statement:

Precautionary Statement:

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. Classification M-factor.
DI Water		7732-18-5			50 - 60%
Potassium Sulfite		10117-38-1	233-321-1		10 - 20%
Hydroquinone		123-31-9	204-617-8		1 - 10% Xn; R22-40-68 Xi; R41-43 N;
Potassium Hydroxide	019-002-00-8	1310-58-3	215-181-3		R50 1 - 10% Xn; R22 C; R35
Potassium Carbonate		584-08-7	209-529-3		1 - 10% Xi; R36/37/38
Pentasodium DTPA Solution 42%		140-01-2	205-391-3		1 - 5% C; R35 Xn; R22-40
Diethylene glycol	603-140-00-6	111-46-6	203-872-2		1 - 10% Xn; R22
Sodium Tetraborate		12179-04-3	215-540-4		1 - 5%
Hydroxymethylphenidone (Dimezone-S)		13047-13-7	235-920-3		1 - 5% XI; R36/37/38

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Conc. Classification	M-factor.
Parties -		1000000000		Number (%w/w)	
DI Water		7732-18-5		50 - 60%	
Potassium Sulfite		10117-38-1	233-321-1	10 - 20%	
was a second					
Hydroquinone		123-31-9	204-617-8	1 - 10% Acute Tox. 4: H302; Skin	
				Sens, 1: H317; Eye Dam	. 1:
				H318; Muta, 2: H341; Ca	rc.
				2; H351; Aquatic Acute 1	
				H400;	
Potassium Hydroxide	019-002-00-8	1310-58-3	215-181-3	1 - 10% Acute Tox. 4: H302; Skin	
				Corr. 1A: H314;	
Potassium Carbonate		584-08-7	209-529-3	1 - 10% Skin lmt. 2: H315; Eye In	rit. 2:
				H319; STOT SE 3: H335	
Pentasodium DTPA Solution 42%		140-01-2	205-391-3	1 - 5% Eye Dam. 1: H318; Acute	
				Tox. 4: H332;	
Diethylene glycol	603-140-00-6	111-46-6	203-872-2	1 - 10% Acute Tox. 4: H302;	
Sodium Tetraborate		12179-04-3	215-540-4	1 - 5% Eye Init. 2: H319;	
Hydroxymethylphenidone		13047-13-7	235-920-3	1 - 5% Acute Tox. 4; H302; Skin	
(Dimezone-S)				Sens. 1: H317;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek
	medical attention.



1118869 5L Imagelink Microfilm Developer and Replenisher

Revision date 4.1. Description of first aid measures Eye contact Causes burns. Causes severe inflammation and may damage the cornea, Seek medical attention. Skin contact Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist. Ingestion Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label. SECTION 5: Firefighting measures 5.1. Extinguishing media Not applicable. This product is not flammable. 5.2. Special hazards arising from the substance or mixture Corrosive. Burning produces imitating, toxic and obnoxious fumes. 5.3. Advice for firefighters Protective equipment. Wear suitable respiratory equipment when necessary. In case of fire and/or explosion do not breathe fumes. SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable 6.2. Environmental precautions Do not allow product to enter drains. Prevent further spillage if safe. 6.3. Methods and material for containment and cleaning up Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water SECTION 7: Handling and storage 7.1. Precautions for safe handling Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. 7.2. Conditions for safe storage, including any incompatibilities Keep in a dry, well ventilated area. Keep containers tightly closed. SECTION 8: Exposure controls/personal protection 8.1. Control parameters 8.1.1. Exposure Limit Values



1118869 5L Imagelink Microfilm Developer and Replenisher

Revision date

8.1.1. Exposure Limit Values

Diethylene glycol	WEL 8-hr limit ppm: 23	WEL 8-hr limit mg/m3: 101
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
lydroquinone	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 0.5
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
otassium Hydroxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls





Ensure adequate ventilation of the working area.

8.2.1. Appropriate engineering

controls

8.2.2. Individual protection

measures

Eye / face protection

Respiratory protection

Skin protection -

Handprotection

Approved safety goggles.

Chemical resistant gloves (PVC).

Wear chemical protective clothing.

Wear:. Self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aqueous solution
Colour	Light yellow
Odour	Characteristic
Partition coefficient	Not relevant
(n-octanol/water)	l l
Autoignition temperature	Not relevant
Decomposition temperature	No data available
Viscosity	Not determined
Odour threshold	Not relevant
рН	10.7
Melting point	Not relevant
Initial boiling point	Not determined
Evaporation rate	Not relevant
Upper Explosive Limit	Not relevant
Lower Explosive Limit	Not relevant
Vapour pressure	Not relevant
Vapour density	Not relevant
Solubility	Soluble in water

Revision Revision date 9.2. Other information Specific gravity 1.335 SECTION 10: Stability and reactivity 10.1. Reactivity No dangerous reaction known. 10.2. Chemical stability Stable under normal conditions. 10.3. Possibility of hazardous reactions No dangerous reaction known. 10.4. Conditions to avoid See "Fire Fighting Measures". 10.5. Incompatible materials No relevant information available. 10.6. Hazardous decomposition products No dangerous decomposition products known. SECTION 11: Toxicological information 11.1. Information on toxicological effects Skin corrosion/irritation May cause irritation to skin. Prolonged or repeated exposure may cause irritation to skin and Repeated or prolonged May cause allergic reactions in susceptible people. May cause severe irritation to eyes and skin. exposure 11.1.4. Toxicological Information No data available SECTION 12: Ecological information 12.1. Toxicity No data available Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 12.2. Persistence and degradability No data is available on this product. 12.3. Bioaccumulative potential No data is available on this product. Partition coefficient Pentasodium DTPA Solution <0 42% 12.4. Mobility in soil No data is available on this product. 12.5. Results of PBT and vPvB assessment Not applicable.

General information

12.6. Other adverse effects

No other relevant information available.

Revision

1118869 5L Imagelink Microfilm Developer and Replenisher

		Revision date	E
General information		, which date	
	Dispose of in compliance with all local and national regulations,		_
Disposal methods	The state of the s		_
	Do not empty into drains; dispose of this material and its container in a safe way. Do NOT mix with		_
	any other product. Do not empty into drains, dispose of this material and its container in a safe way. Do NOT mix with		
	or special waste collection point.		
SECTION 14: Transport information	on a second seco		2 3
14.1. UN number			
	The product is not classified as dangerous for carriage.		_
14.2. UN proper shipping name			_
	The product is not classified as dangerous for carriage.	118	_
14.3. Transport hazard class(es)			_
	The product is not classified as dangerous for carriage.		_
14.4. Packing group	posterior statement are dangerous for carriage.		
	The product is not classified as dangerous for carriage.		
14.5. Environmental hazards	The product is not classified as dangerous for camage.		_
THE ENTIRE HISTORIAN PROCESSION			
	The product is not classified as dangerous for carriage.		
14.6. Special precautions for user			
	The product is not classified as dangerous for carriage.		
	See "Exposure Controls / Personal Protection.		
14.7. Transport in bulk according to Ar	nex II of MARPOL 73/78 and the IBC Code		
	The product is not classified as dangerous for carriage.		
SECTION 15: Regulatory informati	on		
Further information			
	Information contained in the MSDS is to our best present knowledge correct and complete and is		
	given in good faith but without warranty.		
SECTION 16: Other information			980
Other information			
Revision	This document differs from the previous version in the following areas:.		
	14 - ADR/RID.		
	14 - IMDG.		
	14 - IATA.		
Text of risk phrases in Section	R22 - Harmful if swallowed.		
	R35 - Causes severe burns.		
	R36/37/38 - Irritating to eyes, respiratory system and skin. R40 - Limited evidence of a carcinogenic effect.		
	R41 - Risk of serious damage to eyes.		
	R43 - May cause sensitisation by skin contact.		
	R50 - Very toxic to aquatic organisms.		
	R68 - Possible risk of irreversible effects.		
Text of Hazard Statements in	Acute Tox. 4: H302 - Harmful if swallowed.		
Section 3	Skin Sens. 1: H317 - May cause an allergic skin reaction.		
	Eye Dam, 1: H318 - Causes serious eye damage.		
	Muta. 2: H341 - Suspected of causing genetic defects . Carc. 2: H351 - Suspected of causing cancer .		
	Aquatic Acute 1: H400 - Very toxic to aquatic life.		
	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.		
	Skin Irrit. 2: H315 - Causes skin irritation.		
	Eye Irrit. 2: H319 - Causes serious eye irritation.		

Copyright © 2016 ChemSoft Limited. All rights reserved.

Page 7/7

1118869 5L Imagelink Microfilm Developer and Replenisher

		Revision date
Other information		
	STOT SE 3: H335 - May cause respiratory irritation. Acute Tox. 4: H332 - Harmful if inhaled.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in	
	combination with any other materials or in any other process.	