

SOLID POWER XL

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name

: SOLID POWER XL

Other means of identification :

Not applicable.

Recommended use

Machine Warewashing Detergent

Restrictions on use

Reserved for industrial and professional use.

Product dilution information

0.06 % - 0.15 %

Company

Ecolab Co.

5105 Tomken Road

Mississauga, Ontario Canada L4W 2X5

1-800-352-5326

Emergency health

information

1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date

03/08/2017

Section: 2. HAZARDS IDENTIFICATION

GHS Classification

Product AS SOLD

Skin corrosion

Category 1A

Serious eye damage

: Category 1

Product AT USE DILUTION

Not a hazardous substance or mixture.

GHS Label element

Product AS SOLD

Hazard pictograms

(FE)

Signal Word

: Danger

Hazard Statements

: Causes severe skin burns and eye damage.

Precautionary Statements

Prevention:

Wash skin thoroughly after handling.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.IF INHALED: Remove person to fresh air and keep

comfortable for breathing. Immediately call a POISON

CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Wash contaminated clothing before reuse.

Storage:

Store locked up.

SOLID POWER XL

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Product AT USE DILUTION

Precautionary Statements

Prevention:

Wash hands thoroughly after handling.

Response:

Get medical advice/ attention if you feel unwell.

Storage:

Store in accordance with local regulations.

Product AS SOLD

Other hazards

: None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product AS SOLD

Pure substance/mixture

Mixture

Chemical Name

CAS-No.

Concentration: (%)

sodium hydroxide

1310-73-2

60 - 100

Product AT USE DILUTION

No hazardous ingredients

Section: 4. FIRST AID MEASURES

Product AS SOLD

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use

a mild soap if available. Wash clothing before reuse. Thoroughly clean

shoes before reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention

immediately.

If inhaled : Remove to fresh air, Treat symptomatically, Get medical attention if

symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal

protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and

delayed

: See Section 11 for more detailed information on health effects and

symptoms.

Product AT USE DILUTION

In case of eye contact

: Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

SOLID POWER XL

If swallowed : Rinse mouth, Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

Specific hazards during

firefighting

: Not flammable or combustible.

Hazardous combustion

products

: Decomposition products may include the following materials:

Carbon oxides

nitrogen oxides (NOx)

Sulphur oxides

Oxides of phosphorus

Special protective equipment

for firefighters

: Use personal protective equipment.

Specific extinguishing

methods

: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire

and/or explosion do not breathe fumes.

Risk of explosion.

: Not available.

Section: 6. ACCIDENTAL RELEASE MEASURES

Product AS SOLD

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures

listed in sections 7 and 8.

Environmental precautions

: Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up

: Sweep up and shovel into suitable containers for disposal.

Product AT USE DILUTION

Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

Environmental precautions

: No special environmental precautions required.

Methods and materials for containment and cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not

SOLID POWER XL

reach a waterway.

Section: 7. HANDLING AND STORAGE

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not

breathe dust/fume/gas/mist/vapours/spray. Use only with adequate

ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in

suitable labeled containers.

Storage temperature : -10 °C to 50 °C

Product AT USE DILUTION

Advice on safe handling : Wash hands after handling. For personal protection see section 8.

Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
sodium hydroxide	1310-73-2	(c)	2 mg/m3	CAD AB OEL
		Ċ	2 mg/m3	CAD BC OEL
		С	2 mg/m3	OEL (QUE)
sodium hydroxide	1310-73-2	Ceiling	2 mg/m3	ACGIH
		Ceiling	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Personal protective equipment

Eye protection : Due to the form and packaging of the product, no protective

equipment is needed under normal use conditions.

Hand protection : Due to the form and packaging of the product, no protective

equipment is needed under normal use conditions.

Skin protection : Due to the form and packaging of the product, no protective

equipment is needed under normal use conditions.

Respiratory protection : Due to the form and packaging of the product, no protective

equipment is needed under normal use conditions.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes

and body in case of contact or splash hazard.

SOLID POWER XL

Engineering measures : Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Personal protective equipment

Eye protection : No special protective equipment required.

Hand protection : No special protective equipment required.

Skin protection : No special protective equipment required.

Respiratory protection : No personal respiratory protective equipment normally required.

Product AT USE DILUTION

liquid

colourless

odourless

10.11 - 10.91

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Product AS SOLD

Appearance : Cast Solid

Colour : opaque, white

Odour : odourless

pH : 12.5 - 12.8, 1%

Flash point : Not applicable.

Odour Threshold : no data available

Melting point/freezing point : no data available

Initial boiling point and boiling range

Evaporation rate : no data available

Flammability (solid, gas) : no data available
Upper explosion limit : no data available

Lower explosion limit : no data available

Vapour pressure : no data available

Relative vapour density : no data available
Relative density : no data available

Water solubility : no data available
Solubility in other solvents : no data available

Partition coefficient: n-

octanol/water

: no data available

: no data available

Auto-ignition temperature : no data available

Thermal decomposition : no data available

Viscosity, kinematic : no data available

Explosive properties : no data available

Oxidizing properties : no data available

Molecular weight : no data available

VOC : no data available

Section: 10. STABILITY AND REACTIVITY

SOLID POWER XL

Product AS SOLD

Chemical stability

: Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid

: None known.

Incompatible materials

: Acids Metals

Organic materials

Hazardous decomposition

products

: Decomposition products may include the following materials:

Carbon oxides

nitrogen oxides (NOx)

Sulphur oxides

Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Eye contact, Skin contact

exposure

Potential Health Effects

Product AS SOLD

Eyes

: Causes serious eye damage.

Skin

: Causes severe skin burns.

Ingestion

: Causes digestive tract burns.

Inhalation

: May cause nose, throat, and lung irritation.

Chronic Exposure

: Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes

: Health injuries are not known or expected under normal use.

Skin

Health injuries are not known or expected under normal use.

Ingestion

: Health injuries are not known or expected under normal use.

Inhalation

: Health injuries are not known or expected under normal use.

Chronic Exposure

: Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eve contact

: Redness, Pain, Corrosion

Skin contact

: Redness, Pain, Corrosion

Ingestion

Corrosion, Abdominal pain

Inhalation

: Respiratory irritation, Cough

Product AT USE DILUTION

SOLID POWER XL

Eye contact : No symptoms known or expected.

Skin contact: No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Toxicity

Product AS SOLD Product

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

Skin corrosion/irritation : no data available

Serious eye damage/eye : no data available

irritation

Respiratory or skin : no data available

sensitization

Carcinogenicity : no data available
Reproductive effects : no data available

Germ cell mutagenicity : no data available
Teratogenicity : no data available

STOT - single exposure : no data available STOT - repeated exposure : no data available

Aspiration toxicity : no data available

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD Ecotoxicity

Environmental Effects : Harmful to aquatic life.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other : no data available

aquatic invertebrates

Toxicity to algae : no data available

Components

Toxicity to daphnia and other : sodium hydroxide aquatic invertebrates : sodium hydroxide 48 h EC50: 40 mg/l

Persistence and degradability

Product AS SOLD

Biodegradable

Product AT USE DILUTION

Readily biodegradable.

SOLID POWER XL

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Product AS SOLD

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or

used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste

disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to

an approved waste handling site for recycling or disposal. Do not reuse empty containers. Dispose of in accordance with local, state, and

federal regulations.

Product AT USE DILUTION

Disposal methods : Diluted product can be flushed to sanitary sewer.

Disposal considerations : Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (TDG)

UN number : 1823

Description of the goods : SODIUM HYDROXIDE, SOLID

Class : 8
Packing group : II
Environmentally hazardous : No

Sea transport (IMDG/IMO)

UN number : 1823

Description of the goods : SODIUM HYDROXIDE, SOLID


Class : 8
Packing group : II
Marine pollutant : No

Section: 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

SOLID POWER XL



Issuing date

: 03/08/2017

Version

: 1.2

Prepared by

: Regulatory Affairs 1-800-352-5326

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.