

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 27-Jul-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: STEP DOWN

Product Number: 0065

Recommended Use: Stripping solution

Uses Advised Against: For Industrial and Institutional Use Only

Spartan Chemical Company, Inc. Manufacturer/Supplier:

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 1 Sub-category B

Serious Eye Damage/Eye Irritation: Category 1 Specific Target Organ Toxicity (Single Category 3

Exposure):

Corrosive to Metals: Category 1

GHS Label Elements

Signal Word: Danger

Symbols:

Causes severe skin burns and serious eye damage. **Hazard Statements:**

May cause respiratory irritation. May cause drowsiness or dizziness

May be corrosive to metals.

Precautionary Statements:

Do not breathe mist, vapors or spray. Prevention:

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Use only outdoors or in a well-ventilated area.

Keep in original or other corrosion resistant container.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Response: -Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water -Skin

or shower. Wash contaminated clothing before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for -Inhalation:

breathing

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. -Ingestion:

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Spill: Absorb spillage to prevent material damage.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in

corrosion resistant container.

Disposal: Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information: • Corrosive.

· Harmful or fatal if swallowed.

· Harmful contact may not cause immediate pain.

· Harmful if absorbed through skin.

· Take off and destroy contaminated shoes.

· Keep out of reach of children.

• NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

lavage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	40-70
benzyl alcohol	100-51-6	10-30
monoethanolamine	141-43-5	5-10
sodium xylene sulfonate	1300-72-7	1-5
dicarboxylic fatty acid	53980-88-4	1-5
sodium hydroxide	1310-73-2	1-5
alcohol ethoxylate	68439-46-3	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Take off immediately all contaminated clothing and shoes. Rinse with water or shower for

-Skin Contact: Take off immediately all contaminated clothing and shoes. Rinse with water or shower

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse. Discard or destroy contaminated shoes.

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Ingestion: Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR

PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to Physicians: NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

lavage.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Product does not support combustion, Use extinguishing agent suitable for type of

surrounding fire

Specific Hazards Arising from the

Chemical:

-Inhalation:

Dried product is capable of burning. Combustion products are toxic.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and

Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

Precautions for Firefighters: protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Environmental Precautions: Methods for Clean-Up: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Storage Conditions: Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of

children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in

properly labeled containers.

Incompatible Materials: Reactive metals such as aluminum, zinc and tin. Strong acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

	Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Г	monoethanolamine	STEL: 6 ppm	TWA: 3 ppm	IDLH: 30 ppm
	141-43-5	TWA: 3 ppm	TWA: 6 mg/m ³	TWA: 3 ppm
1			(vacated) TWA: 3 ppm	TWA: 8 mg/m ³
ı			(vacated) TWA: 8 mg/m ³	STEL: 6 ppm
			(vacated) STEL: 6 ppm	STEL: 15 mg/m ³
			(vacated) STEL: 15 mg/m³	
	sodium hydroxide	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³	IDLH: 10 mg/m ³
ı	1310-73-2		(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³

Engineering Controls: Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Eye wash stations and shower facilities should be readily accessible in areas where the

product is handled.

Personal Protective Equipment

Eye/Face Protection: Skin and Body Protection: Wear splash goggles. For severe use-conditions, wear a face shield over the goggles. Wear rubber or other chemical-resistant gloves and solvent / alkali resistant boots. The use

of other protective equipment should be considered in order to prevent or minimize contact

with this product.

Respiratory Protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a

NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	Colorless
Odor:	Mild
pH:	13.5-14.0
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	100 °C / 212 °F
Flash Point:	> 100 °C / > 212 °F ASTM D56
Evaporation Rate:	< 1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	1.052
Solubility(ies):	Soluble in water
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight.

Incompatible Materials: Reactive metals such as aluminum, zinc and tin. Strong acids.

Hazardous Decomposition

Products:

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

-Skin Contact: Pain, redness, blistering and possible chemical burn.

-Inhalation: Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and

coughing.

-Ingestion: Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and

diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target Organ Effects: Central nervous system. -Eyes. Respiratory System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 5419 mg/kg
ATEmix (dermal): 5436 mg/kg
ATEmix (inhalation-gas): 3819 mg/l
ATEmix (inhalation-dust/mist): 6 mg/l
ATEmix (inhalation-vapor): 48 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50

water 7732-18-5	> 90 mL/kg(Rat)	Not Available	Not Available
benzyl alcohol 100-51-6	= 1230 mg/kg (Rat)	= 2000 mg/kg (Rabbit)	= 8.8 mg/L (Rat) 4 h
monoethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg (Rabbit) = 1025 mg/kg (Rabbit)	Not Available
sodium xylene sulfonate 1300-72-7	= 7200 mg/kg (Rat)	Not Available	Not Available
sodium hydroxide 1310-73-2	Not Available	= 1350 mg/kg (Rabbit)	Not Available
alcohol ethoxylate 68439-46-3	= 1378 mg/kg (Rat)	> 2 g/kg(Rabbit)	Not Available

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
benzyl alcohol 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	460: 96 h Pimephales promelas mg/L LC50 static 10: 96 h Lepomis macrochirus mg/L LC50 static	Not Available	23: 48 h water flea mg/L EC50
monoethanolamine 141-43-5	15: 72 h Desmodesmus subspicatus mg/L EC50	227: 96 h Pimephales promelas mg/L LC50 flow-through 3684: 96 h Brachydanio rerio mg/L LC50 static 300 - 1000: 96 h Lepomis macrochirus mg/L LC50 static 114 - 196: 96 h Oncorhynchus mykiss mg/L LC50 static 200: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	Not Available	65: 48 h Daphnia magna mg/L EC50
sodium hydroxide 1310-73-2	Not Available	45.4: 96 h Oncorhynchus mykiss mg/L LC50 static	Not Available	Not Available

Persistence and Degradability:

Bioaccumulation:

No information available. No information available.

Other Adverse Effects:

No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes:

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated Packaging:

Dispose of in accordance with federal, state and local regulations.

US EPA Waste Number:

D002

14. TRANSPORT INFORMATION

DOT:

UN/ID No:

UN1760

Proper Shipping Name:

Corrosive liquids, n.o.s., (contains sodium hydroxide, ethanolamine)

Hazard Class: Packing Group:

- 11

Special Provisions:

For totes add: I.B.C.

Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN/ID No: UN1760

Proper Shipping Name: Corrosive liquids, n.o.s., (contains sodium hydroxide, ethanolamine)

Hazard Class: 8
Packing Group: ||

Additional information: For totes add: I.B.C.

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories

Acute Health Hazard:
Chronic Health Hazard:
Fire Hazard:
Sudden release of pressure hazard:
No
Reactive Hazard:
No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA Health Hazards: 3 Flammability: 0 Instability: 0 Special: N/A

HMIS Health Hazards: 3* Flammability: 0 Physical Hazards: 0

Revision Date: 27-Jul-2015 Reasons for Revision: Section 14 and 15

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet