

Material Safety Data Sheet

00116CA Construction Adhesive – Solvent Free – 28 oz cartridge

MSDS No. 0076 – 00116CA

Emergency Phone No.
800-535-5053 - INFOTRAC

SECTION 1 – PRODUCT NAME & MANUFACTURER INFORMATION

PRODUCT NAME	Construction Adhesive – Solvent Free – VOC Compliant		
MANUFACTURER'S NAME & TELEPHONE NUMBER	Red Devil, Inc.	918-825-5744	
STREET ADDRESS	4175 Webb Street		
CITY / STATE / ZIP	Pryor, Oklahoma 74361		

SECTION 2 – COMPOSITION / HAZARDOUS INGREDIENTS

	%	TLV	PEL	UNITS
PRODUCT CONSISTS OF:				
Calcium Carbonate ** (1317-65-3)	< 50	10	15	mg/m3
Acrylic Emulsion (mixture)	< 35	NE	NE	
Benzoate Ester (proprietary)	< 5	NE	NE	
Ammonium Hydroxide (7664-41-7)	< 0.25	25	50	ppm
Non-hazardous ingredients*	< 10	NA	NA	
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Inhalation not likely due to products physical state. Calculated VOC: < 0.5%/wt (< 7 g/L). CARB Compliance: Yes. Prop 65 Ingredients: Yes (See Section 16)				

SECTION 3 – HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF ENTRY	<input checked="" type="checkbox"/> Skin Contact	<input checked="" type="checkbox"/> Skin Absorption	<input checked="" type="checkbox"/> Eye Contact	<input checked="" type="checkbox"/> Inhalation	<input checked="" type="checkbox"/> Ingestion
EMERGENCY OVERVIEW	Off-white colored paste product. Harmful if swallowed.				
EFFECTS OF OVEREXPOSURE	May cause eye, skin, nose, throat & respiratory tract irritation.				
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None known.				

SECTION 4 – FIRST AID MEASURES

SKIN CONTACT	Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.
INHALATION	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.
INGESTION	DO NOT INDUCE VOMITING. Get immediate medical attention.

SECTION 5 – FIRE FIGHTING MEASURES

FLAMMABLE Yes No

EXTINGUISHING MEDIA Carbon Dioxide, Dry Chemical, Foam, Water Fog

FLASHPOINT (°F) & METHOD >200F (Closed Cup)

UPPER EXPLOSIVE LIMIT (% BY VOLUME) NE

LOWER EXPLOSIVE LIMIT (% BY VOLUME) NE

AUTOIGNITION TEMPERATURE (°F) NE

UNUSUAL FIRE & EXPLOSION HAZARDS None known.

SPECIAL FIREFIGHTING PROCEDURES Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PROCEDURES Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.

SECTION 7 – HANDLING & STORAGE

HANDLING PROCEDURES & EQUIPMENT Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing.

STORAGE REQUIREMENTS Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120F. Store away from caustics & oxidizers.

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

RESPIRATORY In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits.

EYEWEAR Goggles or safety glasses w/ side shields.

CLOTHING / GLOVES Rubber gloves. Other protective equipment not required under normal use.

HYGENIC PRACTICES Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE Viscous paste ODOR & APPEARANCE Mild acrylic/ammonia. Smooth paste.

SPECIFIC GRAVITY Approximately 1.0 to 1.50 VAPOR DENSITY (AIR=1) Heavier than air

EVAPORATION RATE Slower than n-Butyl Acetate BOILING RANGE (°F) 210 to 220F

pH Approximately 7 to 10 SOLUBILITY IN WATER Slight, before cure.

VAPOR PRESSURE (MM Hg) NE %/WT VOLATILE (TNV) Approximately 25 to 30%

SECTION 10 – STABILITY AND REACTIVITY

STABILITY Yes No Stable under normal conditions.

INCOMPATIBILITY Yes No Incompatible w/ strong bases & oxidizing agents.

CONDITIONS TO AVOID Excessive heat & freezing.

HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.

SECTION 11 – TOXICOLOGICAL INFORMATION / CARCINOGENICITY

ACGIH	Small amount of Silica, crystalline present in Calcium Carbonate & trace residual Formaldehyde present in base emulsion - suspected human carcinogens.
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard.
IARC	Trace residual Formaldehyde: Human carcinogen.
NTP	Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde: Anticipated carcinogen.
DATA WITH POSSIBLE RELEVANCE TO HUMANS	Product contains trace amounts of residual Formaldehyde. OSHA & NTP identify Formaldehyde as a potential carcinogen. IARC identifies Formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, w/ human significance unknown. Rats have shown carcinogenic effects in respiratory system. Risk should be minimal when used w/ adequate ventilation. Maintain adequate ventilation to prevent exposure above OSHA exposure limits.

SECTION 12 – ECOLOGICAL INFORMATION

AQUATIC TOXICITY	Not known or expected under normal use.
------------------	---

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL	Dispose of material in accordance w/ Federal, State & Local regulations.
EPA WASTE CODE IF DISCARDED (40CFR Sec.261)	None.

SECTION 14 – TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION	Shipping information applicable for domestic ground transport only. Different categorization may be necessary if shipped via other modes of transportation &/or to non-domestic destinations. PRODUCT NOT REGULATED BY DOT.
------------------------------	---

SECTION 15 – REGULATORY INFORMATION

CERCLA – SARA HAZARD CATEGORY	Immediate health hazard; chronic health hazard.	U.S. STATE REGS	See Section 16.
SARA 313	None.	TSCA	All ingredients either on TSCA Inventory or exempt.

SECTION 16 – OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

NJ Right-to-Know: (Top 5 Ingredients): Calcium Carbonate (1317-65-3), Base Acrylic Emulsion (mixture), Benzoate Ester (proprietary), Water (7732-18-5), Propylene Glycol (57-55-6). Pennsylvania Right-to-Know (Non-Haz @ >3%): Water (7732-18-5). HMIS Ratings: Health: 1, Flammability: 0, Reactivity: 0, Personal Protection: B. **WARNING**: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (Trace Residual Formaldehyde (50-00-0) in base polymer & Silica, crystalline (14808-60-7) present @ very low levels in calcium carbonate filler.) INTERNATIONAL EMERGENCY NUMBER: 352-323-3500 - INFOTRAC

LEGEND: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

Reviewed By: <u> Larry G. Brandon </u>	VP Technology & General Manager	March 1, 2012
NAME	TITLE	DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.