

1-20-02-01

## MATERIAL SAFETY DATA SHEET

## SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

9556712

PRODUCT NAME : OLD CEILING WHITE  
 IDENTIFICATION NUMBER: 0000200052  
 PRODUCT USE/CLASS :

DATE PRINTED: 05/24/96

NO: 37

SUPPLIER:  
 SEYMOUR OF SYCAMORE  
 917 CROSBY AVENUE  
 SYCAMORE, IL 60178

MANUFACTURER:  
 SEYMOUR OF SYCAMORE  
 917 CROSBY AVENUE  
 SYCAMORE, IL 60178

24 hr. Telephone: (800) 255-3924

24 hr. Telephone: (800) 255-3924

PREPARER: WGZ, PHONE: 815-895-9101, PREPARE DATE: 01/19/96

## SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	Propane	00074-98-6	20.0 %
02	N-Butane	00106-97-8	15.0 %
03	Toluol	00108-88-3	10.0 %
04	Xylene	01330-20-7	10.0 %
05	Acetone	00067-64-1	10.0 %
06	Titanium Dioxide	13463-67-7	10.0 %
07	Methanol	00067-56-1	5.0 %
08	SC 100 Solvent	64742-95-6	5.0 %
09	UM&P Naphtha	64742-89-8	5.0 %
10	Ethyl Benzene	00100-41-4	5.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH		OSHA		COMPANY	SKIN
TLU-TWA	TLU-STEL	PEL-TWA	PEL-CEILING	TLU-TWA		
01	1000 ppm	N.E.	1000 ppm	N.E.	N.E.	NO
02	800 ppm	N.E.	800 ppm	N.E.	N.E.	NO
03	50 ppm	N.E.	100 ppm	150 ppm	N.E.	YES
04	100 ppm	150 ppm	100 ppm	150 ppm	N.E.	YES
05	750 ppm	1000 ppm	750 ppm	1000 ppm	N.E.	YES
06	5 mg/m3	N.E.	5 mg/m3	N.E.	N.E.	NO
07	200 ppm	250 ppm	200 ppm	250 ppm	N.E.	YES
08	N.E.	N.E.	N.E.	N.E.	N.E.	YES
09	300 PPM	400 PPM*	300 PPM	400 PPM	N.E.	YES
10	100 ppm	125 ppm	100 ppm	125 ppm	N.E.	NO

(See Section 16 for abbreviation legend), \* - Ceiling Value

(Continued on Page 2)

**SECTION 3 - HAZARDS IDENTIFICATION**

NO. 3

**\*\*\* EMERGENCY OVERVIEW \*\*\*:** May cause flash fire or explosion.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Causes skin irritation. Allergic reactions are possible. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**EFFECTS OF OVEREXPOSURE - INHALATION:** Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

**EFFECTS OF OVEREXPOSURE - INGESTION:** This material may be harmful or fatal if swallowed. Irritating to mouth, throat and stomach.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Possible reproductive hazard.

**PRIMARY ROUTE(S) OF ENTRY:** SKIN ABSORPTION INHALATION INGESTION EYE CONTACT SKIN CONTACT

**SECTION 4 - FIRST AID MEASURES**

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

**FIRST AID - SKIN CONTACT:** Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**SECTION 5 - FIRE FIGHTING MEASURES**

FLASH POINT: -4 F

LOWER EXPLOSIVE LIMIT: 0.9 %  
UPPER EXPLOSIVE LIMIT: 36.8 %

(Continued on Page 3)

NO: 37

**SECTION 5 - FIRE FIGHTING MEASURES**

**AUTOIGNITION TEMPERATURE:**

**EXTINGUISHING MEDIA:** WATER FOG DRY CHEMICAL CO2 ALCOHOL FOAM FOAM

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Vapors may form explosive mixture with air.

**SPECIAL FIREFIGHTING PROCEDURES:** Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

**SECTION 7 - HANDLING AND STORAGE**

**HANDLING:** Wash thoroughly after handling.

**STORAGE:** Keep away from heat, sparks and flame.

**SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** Local exhaust ventilation may be necessary to control any air contaminants to within their TLUs during the use of this product.

**RESPIRATORY PROTECTION:** A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**SKIN PROTECTION:** Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.

**OTHER PROTECTIVE EQUIPMENT:** Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

NO. 3

**SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

HYGIENIC PRACTICES: No Information.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

BOILING RANGE	: -44 - 344 F	VAPOR DENSITY	: Is heavier than air
ODOR	: AROMATIC	ODOR THRESHOLD	: NA
APPEARANCE	: LIQUID	EVAPORATION RATE	: Is faster than Ether
SOLUBILITY IN H2O	: SLIGHT	SPECIFIC GRAVITY	: 0.8328
FREEZE POINT	: NA	pH @ 0.0 %	: NA
VAPOR PRESSURE	: 40 PSI	VISCOSITY	: NA
PHYSICAL STATE	: LIQUID		
COEFFICIENT OF WATER/OIL DISTRIBUTION:			

(See Section 16 for abbreviation legend)

**SECTION 10 - STABILITY AND REACTIVITY**

CONDITIONS TO AVOID: Do not store above 120 deg. F. Keep away from sparks, pilot lights, and/or open flames.

INCOMPATIBILITY: No Information.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce hazardous fumes when heated to decomposition. Fumes may contain carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

**SECTION 11 - TOXICOLOGICAL PROPERTIES**

**SECTION 12 - ECOLOGICAL INFORMATION**

ECOLOGICAL INFORMATION: This product does not contain chlorinated solvents or lead.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact.

**SECTION 14 - TRANSPORTATION INFORMATION**

NO. 376

DOT PROPER SHIPPING NAME: CONSUMER COMMODITY ORM-D

DOT TECHNICAL NAME: N/A

DOT HAZARD CLASS: N/A

HAZARD SUBCLASS:

DOT UN/NA NUMBER:

PACKING GROUP:

RESP. GUIDE PAGE:

**SECTION 15 - REGULATORY INFORMATION**

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT/WT % IS LESS THAN
Toluol	00108-88-3	10.0 %
Xylene	01330-20-7	10.0 %
Acetone	00067-64-1	10.0 %
Methanol	00067-56-1	5.0 %
Ethyl Benzene	00100-41-4	5.0 %

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
Water	07732-18-5
Calcium Carbonate	01317-65-3

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
Water	07732-18-5

NO. 37

SECTION 15 - REGULATORY INFORMATION

----- CHEMICAL NAME ----- CAS NUMBER  
 Calcium Carbonate 01317 65 3

**CALIFORNIA PROPOSITION 65:**  
**WARNING:** The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer or birth defects and other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER  
 Toluol 00108-88-3

**INTERNATIONAL REGULATIONS: AS FOLLOWS -**

**CANADIAN WHMIS:** This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

**CANADIAN WHMIS CLASS:** No information available.

SECTION 16 - OTHER INFORMATION

**HMIS RATINGS - HEALTH: 1      FLAMMABILITY: 3      REACTIVITY: 3**

**PREVIOUS MSDS REVISION DATE: 08/07/95**

**LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
 N.D. - Not Determined**

**WARNING: THIS PRODUCT CONTAINS A CHEMICAL  
 OR CHEMICALS KNOWN TO THE STATE  
 OF CALIFORNIA TO;  
 A) CAUSE CANCER  
 OR  
 B) CAUSE BIRTH DEFECTS OR OTHER  
 REPRODUCTIVE HARM.  
 (22 Cal. Code 12601 (b) (5))**

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

<END OF MSDS>