

MSDS - Material Safety Data Sheet**Product Name: NAPA MAC 6300 - PENETRATING LUBRICANT**

MSDS No.: 6300

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY
Address: 600 RADIATOR ROAD
City, ST Zip: INDIAN TRAIL, NC 28079
Country: USA

Contact: Robert Geer
Information Telephone Number: 704-684-1811
Emergency Contact: RMPDC (877-740-5015)
Emergency Telephone Number: 303-623-5716
Emergency Restrictions:

Product Name: NAPA MAC 6300 - PENETRATING LUBRICANT
MSDS No.: 6300

Issue Date: 10/31/2013**Supersedes Date:** 07/08/2010**II. Hazards Identification:****EMERGENCY OVERVIEW**

Danger: Flammable. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Contents under pressure.

Level 3 Aerosol

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects**Route(s) of Entry:**

Absorption, Inhalation, and Ingestion.

Health Hazards (Acute and Chronic):

See signs and symptoms below

Signs and Symptoms:

Eye Contact: May cause slight irritation

Skin Contact: May cause slight irritation

Inhalation: If oil mist is inhaled for prolonged periods, may cause irritation.

Ingestion: Can be Harmful or fatal if swallowed.

Medical Conditions Generally Aggravated by Exposure:

None known

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

Potential Environmental Effects

Not Available

III. Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
1,2,4-Trimethylbenzene	95-63-6	1.0 - 5.0	
2-Butoxyethoxy-2-ethanol	112-34-5	1.0 - 5.0	
Aliphatic Hydrocarbon Solvent	8052-41-3	10.0 - 30.0	
Carbon dioxide	124-38-9	1.0 - 5.0	
Hydrocarbon Fluid	64742-47-8	15.0 - 40.0	
Isopropylbenzene	98-82-8	0.1 - 1.0	
Naphthenic Petroleum Distillate	64742-52-5	60.0 - 100.0	
Trimethyl benzene	25551-13-7	1.0 - 5.0	

IV. First Aid Measures:

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids and get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

Note to Physicians:

N/E

V. Fire Fighting Measures:

Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, Dry Chemical

Unsuitable Extinguishing Media:

Do not use forced water stream as this could cause the fire to spread.

Products of Combustion:

Carbon dioxide, carbon monoxide, and various hydrocarbons

Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

VI. Accidental Release Measures:

Personal Precautions:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

Methods for Containment:

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

Methods for Cleanup:

Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

Other Information:

If run-off occurs, notify proper authorities as required that a spill has occurred.

VII. Handling and Storage:

Handling Precautions:

Handling: Use with adequate ventilation and proper protective equipment.

Do not use or store near fire, sparks, or flame. Exposure to temperatures above 120° may cause container to vent, rupture, or burst.

Storage Precautions:

Keep container closed tightly when not in use.

Store in a cool place away from oxidizing agents.

VIII. Exposure Controls/Personal Protection:

MSDS - Material Safety Data Sheet**Product Name: NAPA MAC 6300 - PENETRATING LUBRICANT**

MSDS No.: 6300

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Naphthenic Petroleum Distillate	5 mg/m ³	5 mg/m ³	Not Available
Aliphatic Hydrocarbon Solvent*	100 ppm	100 ppm	Not Available
Trimethyl benzene	25 ppm (TWA)	25 ppm (TWA)	Not Available
Isopropylbenzene	50 ppm	50 ppm	Not Available
Hydrocarbon Fluid	5 mg/m ³	5 mg/m ³	Not Available
2-Butoxyethoxy-2-ethanol	N/E	N/E	35 ppm
1,2,4-Trimethylbenzene	N/E	25 ppm	Not Available
Carbon dioxide	N/AV	5000 ppm	Not Available

Engineering Controls:

See above Section for applicable exposure limits. Maintain adequate ventilation. Avoid breathing mist. In restricted areas, use approved chemical filters designed to remove mist. In confined areas, use approved air line type respirator or hood. A self-contained breathing apparatus is required for vapor or mist concentrations above TLV limit

Personal Protective Equipment:

For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: 157° F

Boiling Range: N/D

Solubility In Water: Insoluble

Flash Point: > 132° F

Odor Threshold: N/D

Vapor Density (AIR = 1): N/D

pH Range: N/A

Decomposition Temp: N/D

Lower Explosive Limit: N/D

Specific Gravity (H₂O = 1): 0.86

Other Information: VOC CONTENTS: < 24%

Melting Point: N/D

Freezing Point: N/D

Evaporation Rate (Butyl Acetate = 1): Slow

Flash Point Method: TCC

Appearance and Odor: Clear amber oil with petroleum odor

Vapor Pressure (mm Hg.): N/D

Partition Coefficient: N/D

Auto-Ignition Temp: N/D

Upper Explosive Limit: N/D

X. Stability and Reactivity:**Stability:**

Stable

Conditions to Avoid:

Avoid heat, sparks, and flames. Avoid incompatible materials.

Incompatible Materials:

Avoid contact with strong oxidizing agents

Hazardous Decomposition Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, phosphorus, nitrogen and sulfur oxides.

Possibility of Hazardous Reactions:

Will not occur

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the empty container and discard in the trash. Do not dump into sewers, on the ground, or into any body of water. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:

Shipping Name: See below

DOT Hazard Class: Not Available

DOT Subsidiary Hazard Class: Not Available

UN/NA#: Not Available

Packing Group: Not Available

Transportation Information:

DOT Shipping Name: CONSUMER COMMODITY

DOT Hazard Class: ORM-D

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping purposes.

ICAO/IATA (US)

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

International:

ICAO/IATA

UN number: UN1950

Shipping Name: Aerosols

Class: 2.1

IMDG

UN number: UN1950

Shipping Name: Aerosols

Class: 2.1

EmS: F-D, S-U

XV. Regulatory Information:

SARA 313 Reportable Chemicals

Aliphatic Hydrocarbon Solvent 8052-41-3

Isopropylbenzene 98-82-8

2 Butoxyethoxy-2-ethanol 112-34-5

1,2,4-Trimethylbenzene 95-63-6

Ethylbenzene 100-41-4

USA TSCA: All components of this material are listed on the US TSCA Inventory.

Warning: This product contains a chemical known to the State of California to cause cancer or birth defects or other reproductive harm.

State RTK Chemicals:

Aliphatic Hydrocarbon Solvent 8052-41-3

Isopropylbenzene 98-82-8

2 Butoxyethoxy-2-ethanol 112-34-5

1,2,4-Trimethylbenzene 95-63-6

Ethylbenzene 100-41-4

Hydrocarbon Fluid 64742-47-8


MSDS - Material Safety Data Sheet

Product Name: NAPA MAC 6300 - PENETRATING LUBRICANT

MSDS No.: 6300


XVI. Other Information:

Chemical State: Liquid Gas Solid
Chemical Type: Pure Mixture
Hazard Category:
 Acute Chronic Fire
 Pressure Reactive



Additional Manufacturer Warnings:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!



N/E: Not Established
 N/D: Not Determined
 N/A: Not Applicable
 N/AV: Not Available

Additional Product Information:

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.

